



Main Features

- 🔊 Warrior black paint colour scheme with badges
- 🔊 Stainless steel exhaust
- 🔊 Deutz Tier 3- 171Hp 6.1 Lt Turbocharged engine with 699nm max torque – NO AdBlue + DPF
- 🔊 50km/h Automatic RC-Shift transmission – 54 Forward + 27 Reverse gears including creep range
- 🔊 MaxiVision II deluxe cabin with Automatic climate control + carpet floor mat
- 🔊 MaxCom armrest control
- 🔊 Full work light package with 14 work lights
- 🔊 Grammer Max Dynamic Plus XXL seat with dynamic dampening and heater
- 🔊 Mechanical cabin suspension
- 🔊 Dynamic front axle suspension with 120 mm travel
- 🔊 120 L/min Closed centre hydraulics fitted with 4 Sets of rear remotes
- 🔊 Power beyond and load sense lines
- 🔊 4 Speed PTO
- 🔊 EasySteer hydraulic steering system fitted with Trimble GPS (Trimble GFX750 and NAV 900 Controller – Rangepoint Ready)
- 🔊 ISOBUS 11783 UT connectivity
- 🔊 ComforTip Headland management
- 🔊 3yrs/2500hrs Warranty

Engine

Deutz TCD6_1 LO6 4V Tier 3 Diesel Engine
 6 Cyl/6057cc Turbocharged/Intercooled
 NO AdBlue and DPF
 Electronically Controlled
 4 Valves Per Cylinder
 Liquid/Oil Cooled
 Common Rail DCR Injection System
 171Hp Max power with boost (ECE R-120)
 164Hp Max power (ECE R-120)
 7Hp Power Boost
 Max torque 699nm @1500 rpm
 Engine Speed Programming x 2
 Powercore Air filter with Dust Ejectors
 Side Exhaust
 280Lt Fuel Capacity

Transmission

Wet clutch Powershuttle
 Shuttle modulation – 5 Stage (Sense Clutch)
 RC-shift ZF Robotized Transmission
 54/27 Forward/Reverse Gears
 Creep Gears
 6 speed Powershift with Robotized shifting
 Robotized Shifting = Manual/Semi auto/ Auto Field
 Auto Road with Cruise and De-clutch Function
 Speed Matching
 Front Wheel Assist
 4 Wheel Braking with Power Brake System
 Front Axle Suspension with Adaptive Damping System
 Front & Rear Diff Lock
 ASM Auto Diff Lock & 4wd Engagement
 Radar
 50 km/h Road Speed @ Economy RPM 1969 rpm

PTO

Independent Wet Multidisc Clutch
 4 Speed PTO 540/540E/1000/1000E
 Push Button Control on Armrest
 Auto PTO
 External PTO Start/Stop
 Interchangeable PTO Spline Function
 1" 3/8 – 6 Spline PTO Shaft
 1" 3/8 – 21 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Radial Wheel Equipment
 540/65R28 Front -650/65R38Rear
 Warrior Brilliant Black Paint + Decals
 Stainless Steel Exhaust
 Front Weight Frame with Hitch (100kg)

Operator Environment

MaxiVision 2 Air Conditioned Cab
 Automatic Climate Control
 Mechanical Cabin Suspension
 Cab Roof hatch without Glass
 Double Glazed Rear Lower Cab Glass
 Max Dynamic Plus DDS XXL Deluxe Air Seat
 INFOCENTER Pro Digital Display
 EASY STEER Quick Steer System
 MaxCom Armrest Controls - Adjustable
 COMFORTIP Sequential Drive System
 Padded Trainee Seat with Seatbelt
 Refrigerated/Heated Drink Storage Compartment
 Bluetooth MP3 Audio System
 WOLP (Work Operating Light Panel)
 Telescopic Mirrors
 Hi Beam / Low Beam Bonnet Lights
 2 Bonnet Front Work lights
 8 Cabin Work Lights
 2 Front Work Lights on Cab Post
 2 Rear Work Lights on Cab Post
 Rotating Beacon

Connected Farming Systems

EASY STEER Hydraulic Auto Steer
 Trimble GFX750 with NAV 900
 RangePoint + UT Ready
 ISOBUS 11783 9 pin socket + Internal cab socket
 ISO 11786 7pin socket

Hyd/Linkage/Drawbar

Closed Centre Hydraulic System
 120 L/min Hyd Pump
 Power Beyond Valve and Load Sensing Lines
 Hi Flow & Free Flow Return
 Separate 42L/min Steering Pump
 4 Sets of Electro-Hyd Remotes
 4 Sets Float
 Flow and Timer Control on All Remotes
 External Push Buttons on guard for 1 remote
 AGROTRONIC EHR with position & draft
 Implement Ride Control
 External Raise & Lower on Rear Fenders
 Cat II/III Hook Ends
 9200 kg Lift Capacity
 Swinging Drawbar - CAT 3

Weights & Dimensions

Wheelbase	2767mm
Length	4347mm
Total Height	3032mm
Total Weight	7300 kg