



## Main Features

- 🔊 Warrior black paint colour scheme with badges
- 🔊 Stainless steel exhaust
- 🔊 Deutz Tier 3- 226 Hp 6.1 Lt Turbocharged engine with 889nm max torque – NO AdBlue + DPF
- 🔊 50km/h Automatic RC-Shift transmission – 54 Forward + 27 Reverse gears including creep range
- 🔊 MaxiVision II deluxe cabin with Automatic climate control + carpet floor mat
- 🔊 MaxCom armrest control
- 🔊 Full work light package with 14 work lights
- 🔊 Grammer Max Dynamic Plus XXL seat with dynamic dampening and heater
- 🔊 Mechanical cabin suspension
- 🔊 Dynamic front axle suspension with 120 mm travel
- 🔊 120 L/min Closed centre hydraulics fitted with 4 Sets of rear remotes
- 🔊 Power beyond and load sense lines
- 🔊 4 Speed PTO
- 🔊 EasySteer hydraulic steering system fitted with Trimble GPS (Trimble GFX750 and NAV 900 Controller – Rangepoint Ready)
- 🔊 ISOBUS 11783 UT connectivity
- 🔊 ComforTip Headland management
- 🔊 3yr/2500hrs Warranty

## Engine

Deutz TCD6\_1 LO6 4V Tier 3 Diesel Engine  
 6 Cyl/6057cc Turbocharged/Intercooled  
 NO AdBlue and DPF  
 Electronically Controlled  
 4 Valves Per Cylinder  
 Liquid/Oil Cooled  
 Common Rail DCR Injection System  
 226Hp Max Power with Boost (ECE R-120)  
 212Hp Max Power (ECE R-120)  
 14Hp Power Boost  
 Max Torque 889 nm @1500 rpm  
 Engine Speed Programming x 2  
 Powercore Air Filter with Dust Ejectors  
 Side Exhaust  
 280Lt Fuel Capacity

## Transmission

Wet Clutch Powershuttle  
 Shuttle Modulation – 5 Stage (Sense Clutch)  
 RC-shift ZF Robotized Transmission  
 54/27 Forward/Reverse Gears  
 Creep Gears  
 6 Speed Powershift with Robotized shifting  
 Robotized Shifting = Manual /Semi Auto/ Auto Field  
 Auto Road with Cruise and De-clutch Function  
 Speed Matching  
 Front Wheel Assist  
 4 Wheel Braking with Power Brake System  
 Front Axle Suspension with Adaptive Damping System  
 Front & Rear Diff Lock  
 ASM Auto Diff Lock & 4wd Engagement  
 Radar  
 50 km/h Road Speed @ Super Economy RPM

## PTO

Independent Wet Multidisc Clutch  
 4 Speed PTO 540/540E/1000/1000E  
 Push Button Control on Armrest  
 Auto PTO  
 External PTO Start/Stop  
 Interchangeable PTO Spline Function  
 1" 3/8 – 6 Spline PTO Shaft  
 1" 3/8 – 21 Spline PTO Shaft

## Wheel Equipment & Miscellaneous

Fixed Radial Wheel Equipment  
 540/65R30 Front -650/65R42Rear  
 Dynamic Front Fenders  
 Warrior Brilliant Black Paint + Decals  
 Stainless Steel Exhaust  
 Front Weight Frame (330kg)

## Operator Environment

MaxiVision 2 Air Conditioned Cab  
 Automatic Climate Control  
 Mechanical Cabin Suspension  
 Cab Roof Hatch without Glass  
 Double Glazed Rear Lower Cab Glass  
 Max Dynamic Plus DDS XXL Deluxe Air Seat  
 INFOCENTER Pro Digital Display  
 EASY STEER Quick Steer System  
 MaxCom Armrest Controls - Adjustable  
 COMFORTIP Sequential Drive System  
 Padded Trainee Seat with Seatbelt  
 Refrigerated/Heated Drink Storage Compartment  
 Bluetooth MP3 Audio System  
 WOLP (Work Operating Light Panel)  
 Telescopic Mirrors  
 Hi beam / Low beam Bonnet lights  
 2 Bonnet Front Work lights  
 8 Cabin Work lights  
 2 Front Work lights on Cab post  
 2 Rear Work lights on Cab post  
 Rotating Beacon

## Connected Farming Systems

EASY STEER Hydraulic Auto Steer  
 Trimble GFX750 with NAV 900  
 RangePoint + UT Ready  
 ISOBUS 11783 9 pin socket + Internal cab socket  
 ISO 11786 7pin socket

## Hyd/Linkage/Drawbar

Closed Centre Hydraulic System  
 120 L/min Hyd Pump  
 Power Beyond Valve and load sensing lines  
 Hi Flow & Free Flow return  
 Separate 42L/min Steering Pump  
 4 Sets of Electro-Hyd Remotes  
 Flow and Timer Control on all Remotes  
 External push buttons on guard for 1 remote  
 AGROTRONIC EHR with position & draft  
 Implement Ride Control  
 External Raise & lower on Rear Fenders  
 Cat II/III Hook ends  
 9700 kg lift capacity  
 Swinging Drawbar – CAT 3

## Weights & Dimensions

Wheelbase	2848mm
Length	4937mm
Total Height	3082mm
Total Weight	8100 kg