



Main Features

- 🔔 Warrior black paint colour scheme with badges
- 🔔 Stainless steel exhaust
- 🔔 Deutz Tier 3- 226 Hp 6.1 Lt Turbocharged engine with 889nm max torque
- 🔔 NO AdBlue + DPF
- 🔔 50km/h TTV variable speed transmission
- 🔔 MaxiVision II deluxe cabin with Automatic climate control + carpet floor mat
- 🔔 MaxCom armrest control
- 🔔 Full work light package with 14 work lights
- 🔔 Grammer Max Dynamic Plus XXL seat with dynamic dampening, heater + swivel
- 🔔 Mechanical cabin suspension
- 🔔 Dynamic front axle suspension with 120 mm travel
- 🔔 120 L/min Closed centre hydraulics fitted with 4 Sets of rear remotes
- 🔔 Power beyond and load sense lines
- 🔔 4 Speed PTO
- 🔔 EasySteer hydraulic steering system fitted with Trimble GFX750 Precision Ag system – RangePoint Ready
- 🔔 ISOBUS 11783 UT connectivity
- 🔔 ComforTip Headland management
- 🔔 Front Linkage + PTO (1000 Speed)
- 🔔 Comfort pack front hydraulics – Includes 1 set of front remotes and external linkage controls
- 🔔 3yr/2500hrs Warranty

August 2021

Engine

Deutz TCD6_1 LO6 4V Tier 3 Diesel Engine
6 Cyl/6057cc Turbocharged/Intercooled
NO AdBlue and DPF
Electronically Controlled
4 Valves Per Cylinder
Liquid/Oil Cooled
Common Rail DCR Injection System
226hp Max Power with Boost (ECE R-120)
212hp Max Power (ECE R-120)
14Hp Power Boost
Max Torque 889 nm @1500 rpm
Engine Speed Programming x 2
Powercore Air filter with Dust Ejectors
Side Exhaust
435Lt Fuel Capacity

Transmission

ZF S-Matic 180+CVT Transmission
4 Working Ranges
3 Driving Modes (Auto, PTO, Manual)
Acceleration and Power Adjustment
Speed Cruise Control x 2
Active Stationary Control
Wet Clutch Powershuttle
Shuttle Modulation – 5 Stage (Sense Clutch)
Front Wheel Assist
4 Wheel Braking with Power Brake System
Front Axle Suspension with Adaptive Damping System
Front & Rear Diff Lock
ASM Auto Diff Lock and 4wd Engagement
Radar
Separate Transmission Fluid Reservoir
50 km/h Road Speed @ Economy RPM 1969 rpm

PTO

Independent Wet Multidisc Clutch
4 Speed PTO 540/540E/1000/1000E
Push Button Control on Armrest
Auto PTO
External PTO Start/Stop
Interchangeable PTO Spline Function
1" 3/8 – 6 Spline PTO Shaft
1" 3/8 – 21 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Radial Wheel Equipment
540/65R30 Front -650/65R42Rear
Dynamic Front Fenders
Warrior Brilliant Black Paint + Decals
Stainless Steel Exhaust

Weights & Dimensions

Wheelbase	2848mm
Length	4508mm
Total Height	3160mm
Total Weight	8800 kg

Operator Environment

MaxiVision 2 Air Conditioned Cab
Automatic Climate Control
Mechanical Cabin Suspension
Cab Roof Hatch without Glass
Double Glazed Rear Lower Cab Glass
Max Comfort Dynamic XXL Deluxe Air Seat with Swivel
INFOCENTER Pro Digital Display
WORK Monitor
MaxCom Armrest Controls - Adjustable
COMFORTIP Sequential Drive System
Padded Trainee Seat with Seatbelt
EASY STEER Quick Steer System
Bluetooth MP3 Audio system
WOLP (Work Operating Light Panel)
Telescopic Mirrors
Courtesy LED Entry Light
Hi Beam / Low Beam Bonnet + Cab Post Lights
2 Bonnet Front Work Lights
8 Cabin Work Lights
2 Front Work Lights on Cab Post
2 Rear Work Lights on Cab Post
Rotating Beacon

Connected Farming Systems

EASY STEER Hydraulic Auto Steer
Trimble GFX750 with NAV 900
RangePoint + UT Ready
ISOBUS 11783 9 pin socket + Internal cab socket
ISO 11786 7pin socket

Hyd/Linkage/Drawbar

Closed Centre Hydraulic System
160 L/min Hyd Pump
Power Beyond Valve and Load sensing lines
Hi Flow & Free Flow Return
Separate 42L/min Steering Pump
4 Sets of Electro-Hyd Remotes
Flow and Timer Control on All Remotes
External Push Buttons on Guard for 1 Remote
AGROTRONIC EHR with Position & Draft
Implement Ride Control
External Raise & Lower on Rear Fenders
Cat II/III Hook Ends
9700 kg Lift Capacity
Swinging Drawbar – CAT 3

Front Linkage & PTO

Front Linkage - 5480kg Capacity
Front PTO – 1000N
1 Front Remote & External Raise/lower
Dial Control to operate front linkage