

7010GCRO_english_rev04_0718.indd 1 23/07/2018 14:53:48





Folding wings for easy transportation on models with 52 to 60 and from 72 to 80 folding wing frames.

The model 7010 GCRO is specially designed for large acreage arm operations. It is ideal implement for soil leveling, breaking clods and incorporating soil with crop residue.




STANDARD FEATURES:

- TATU oil bath bearings assemblies with tapered roller blade and duo-cone seals.
- Bolt on heavy duty bearing wear plates.
- 1.5/8" (41.3mm) round heat treated alloy steel gang axles.
- Heat treated boron steel disc blades, notched front and rear.
- Available with 26", 28" or 30" diameter disc blades.
- Cast iron spacer spools.
- Heavy duty adjustable disc blade scrapers.
- Dual heavy duty 8 bolt hubs less tires and wheels. (Recommended 12.5L x 15" - 12 ply tires).
- Hydraulic cylinder control group includes two hydraulic cylinders and hoses ram stops for depth control, transport lock.
- Quick adjustable swing tongue.
- Adjustable gang axles of 18, 20 and 22 degrees.
- Drawbar jackstand and safety chain.
- Wing fold models include hydraulic folding cylinders, hoses and fittings.
- Rear mounted hitch with hydraulic outlet.
- Rear hook for leveling bar.

RUGGEDLY BUILT FOR LONGER LIFE



SPECIAL OIL BATH BEARING ASSEMBLIES



THE LIFE OF YOUR DISK HARROW REQUIRES ORIGINAL TATU REPLACEMENT PARTS.

SPECIFICATIONS:

Model	Number of Disc Blades	Working Width		Disc Blades		Weight per Disc		Approx. Net Weight*	Tractor Draw Bar
		ft. in.	(mm)	Dimensions	Spacing	lbs	(Kg)	lbs (Kg)	Horse Power
7010 GCRO Non Folding	28	12' 1"	(3,680)			388	(176)	10,868 (4,930)	180 - 200
	32	13' 9"	(4,190)			360	(163)	11,530 (5,230)	200 - 220
	36	15' 5"	(4,700)			337	(153)	12,156 (5,514)	220 - 240
	40	17' 1"	(5,205)	26"x6.0mm,		314	(142)	12,575 (5,704)	240 - 260
	44	18' 9"	(5,715)			304	(138)	13,384 (6,071)	260 - 280
	48	20' 5"	(6,220)	28"x7.5mm	10.5/8"	288	(130)	13,829 (6,273)	280 - 300
7010 GCRO Folding Wings	52	22' 1"	(6,730)		(270mm)	310	(141)	16,153 (7,327)	300 - 320
	56	23' 9"	(7,240)	and		298	(135)	16,695 (7,573)	320 - 330
	60	25' 9"	(7,772)			286	(130)	17,193 (7,799)	330 - 350
7010 GCRO Folding Wing Frames	72	31' 3"	(9,540)	30"x7.5mm		423	(192)	30,450 (13,812)	370 - 390
	76	33'	(10,065)			402	(183)	30,617 (13,888)	390 - 410
	80	34' 3"	(10,445)			390	(177)	31,215 (14,159)	410 - 430

^{*} Approx. net weight with 28" x 7.5mm disc blades.

OPTIONAL EQUIPMENT:

- Bolt on furrow filler extension blade.
- Disc blades notched front and plain on rear.
- Disc blades plain front and rear.
- Tapered right rear gang assemblies.

MARCHESAN S.A. reserves the right to perfect or alter the characteristics of its products, without the obligation to do so with those already marketed and without giving prior knowledge. The photos and drawings are merely illustrative. - 07/2018 - Rev. 04









Av. Marchesan, 1979 - CEP 15994-900 - Matão-SP-Brasil Phone: +55 16 3382.8282 - Fax (Sales): 3382.8297 CNPJ.: 52.311.289/0001-63 - Inscr. Est.: 441.000.151.114

www.marchesan.com.br email: tatu@marchesan.com.br

THE BRAND OF THE LAND

7010GCRO_english_rev04_0718.indd 2

> Transport width - 52, 56 and 60 disc blades: 15 ft. 4 in (4,670mm). > Approx. depth of cut: up to 8.5/8" (220mm).