

5110.4D TTV

Specialist Series

Front Linkage + PTO

Engine

FARMotion Tier 4i Diesel Engine
4 Cyl/3849cc Turbocharged/Intercooled
Electronically Controlled
Emission Control by DOC unit
Liquid/Oil Cooled
Electronically Controlled E-Visco Fan
High Pressure Diesel injection common rail
113 Hp Max hp @ 2200 rpm (2000/25/CE)
6 Hp Power Boost
Torque 435 Nm @1600 rpm
Programmable Engine Speed × 2
Powercore Air Filter with Dust Ejectors
Side Vertical Exhaust
Fuel Tank 115 Litres

Transmission

TTV 2 Range Variable Transmission
3 Modes (AUTO, Manual, PTO)
Eco/Power Dial
Speed Cruise Control × 2
Active Stationary Control (Power Zero)
Wet Clutch Powershuttle
Shuttle Modulation – 5 Stage (Sense Clutch)
Front Wheel Assist – Push Button
4 Wheel Independent Braking
Hydraulic Parking Brake (HPB)
100% Front & Rear Diff Lock – Push Button
40km/h Road Speed @ 1650 RPM

PTO

Independent Hydraulic Rear PTO
Push Button
Auto PTO Function
3 Speed PTO 540/750/1000
1" 3/8 – 6 Spline PTO Shaft
Interchangeable PTO Spline Function

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
Front 320/85R20 Rear 380/85R30Rear
Front Weight Frame with Hitch
Rear Swinging Drawbar
Battery Isolator Switch

Front Linkage & PTO

Front Linkage - 1750kg Capacity
Front PTO – 1000N
Push Button PTO Control
Linkage Operated via Separate Remote Switch



Operator Environment

4 Post Air conditioned Cabin with CAT 4 Filtration
Flat Operator Floor
Rear Hinged Roof for High Visibility
Hydro Silent Block Cabin Suspension
Super Deluxe Air Seat with Tilt and Lumbar Support
Tilt and Telescopic Steering Wheel
Armrest Control with MaxCom Joystick
3 Programmable Buttons on MaxCom Joystick
SDD Rapid Steering Circuit
INFOCENTER Pro Digital Display
COMFORTIP Sequential Drive System
MP3 Radio Player with Speakers
Telescopic Mirrors
6 Cabin Work Lights
4 Bonnet Front Work lights
Rotating Beacon
2 External Electrical Sockets

Hyd/Linkage/Drawbar

Closed Centre Hydraulic System
100 l/min Hydraulic Pump
Electro Hyd Remotes Controlled on MaxCom Armrest
4 Sets of Rear High Flow Remotes
2 Sets of Front Remotes duplicated from Rear
1 Rear Free Flow Return
1 Front Free Flow Return
Timer and Flow Control on All Remotes
Separate 42L/min Steering Pump
Electronic 3PL c/w Position & Draft Controls
External Push button Raise and Lower
Cat 2 Hook Ends
4310 kg Lift Capacity
Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase 2271 mm
Length 4060 mm
Total Height 2545mm (Top of Cab)
Min Overall Width 1780mm (Rear wheels)
Cabin Width 1280mm
Total Weight 4258kg